


Product Information Sheet



BEDROCK

Floor Sealer: Base coat for vinyl and terrazzo



Product

- ✓ Assists to level out undulating floor surfaces
- ✓ Provides a barrier that resists stains, water and detergents spills
- ✓ Improves wearability and life of top coat
- ✓ Ready to use



Water based sealer for vinyl, terrazzo and stone surfaces. The smaller particle size of the polymer will penetrate deep into the surface and bonds to the surface for greater adhesion of the top coat. Also BEDROCK will provide increased wear and chemical resistance.

Technical

Colour	Milky white
Odour	Polymer odour
pH	8.50 – 9.50
Solids (%)	18.00
Coverage (m ² /Lit)	40- 50 m ² /L (Typical)

Product Code	Outer Pack	APN
CHRC-610015A (5L)	3	9324828001416
CHRC-61015 (15L)	1	9324828001423

Application

Task	Method
Floor Preparation	<ol style="list-style-type: none">1. Strip off old sealers or finishes with STEAMROLLER II, MELTDOWN or SLEDGEHAMMER as directed.2. Rinse well with warm water and allow it to dry.3. Dust mop entire area.
Application	<ol style="list-style-type: none">1. Apply a thin even coat of BEDROCK using an Oates Poly-cotton mop (MH-PR-24) or a Nylon Polish Spreader (SM-156).2. Allow coating time to completely dry (approximately 45 minutes).3. Apply a second coat (if necessary) or apply the chosen floor finish (2 or 3 coats) after BEDROCK is dried. Do not buff BEDROCK or leave it as a finishing coat - it is a non-buffable sealer.

Safety: Avoid contact with eyes and skin.
Wear impervious chemical resistant gloves and safety goggles before use.

Not considered hazardous according to the criteria of Safe Work Australia.