


Product Information Sheet



BLOCKADE

Floor Sealer: Interior concrete and resilient tiles



Product

- ✓ Exceptional adhesion to concrete surfaces including floors with embedded oil and dirt
- ✓ Remains flexible under all temperature conditions
- ✓ Enhance the appearance of the floor by giving a glossy smooth finish
- ✓ Will not "flick off" in freezer rooms or turn yellow
- ✓ Protect the substrate from staining and damage by chemicals
- ✓ Can be used in food processing factories without the need to remove food items from the site



Ideal base-sealer providing an abrasion resistant coating for concrete, stone and terrazzo. Forklift traffic leaves a very low level of tyre mark transfer. Recoats easily and unlike epoxies and urethanes, it can be cleaned and recoated without inter-coat hazing or delamination occurring. Suitable for use as a base seal over old oily floors. Easy to apply.

Technical

Colour	Milky White
Odour	Polymer Odour
pH	7.50 – 8.50
Solids (%)	21.00
Coverage (m ² /Lit)	1 st coat: 20-30 m ² /L 2 nd and 3 rd coats: 30-40m ² /L

Product Code	Outer Pack	APN
CHRC-570015A (5L)	3	9324828000488
CHRC-57015 (15L)	1	9324828000495

Application

Task	Method
Preparation	<ol style="list-style-type: none">1. Ensure the surface is free from grease and dirt. Also make sure any old coatings have been removed.2. To clean the surface, use CROSSFIRE as directed. For the removal of any other water based old coatings or curing oils, use MELTDOWN as directed.3. Once all contamination is removed, rinse well with clean water and allow it to dry.
Sealer application	<ol style="list-style-type: none">1. BEDROCK can be applied with the lambswool applicator, Oates poly-cotton lint free mop or nylon polish spreader.2. Steel trowelled (smooth) concrete: 1st coat: Approximately 30m²/L 2nd and subsequent coats: Approximately 40m²/L Wood floated (rough) concrete and rough stone: 1st coat: Approximately 20m²/L 2nd and subsequent coats: Approximately 30m²/L Exfoliated Granite and Terrazzo: 1st coat: Approximately 20m²/L 2nd and subsequent coats: Approximately 40m²/L3. Apply chosen floor finish and apply 2 to 3 coats after BLOCKADE is dried.
Maintenance	Mop or auto scrub with SUPASTAR as directed.

Safety: Avoid contact with eyes and skin.

Wear impervious chemical resistant gloves and safety goggles before use.

Not considered hazardous according to the criteria of Safe Work Australia.

Version: 1 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au.
This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



E.D. Oates Pty Ltd ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows VIC 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

Oates is a division of GUD Holdings Ltd (ABN 99 004 400 891)