



T560

Micro ride-on floor scrubber

The T560 micro ride-on floor scrubber is compact and tailored for commercial spaces. Designed for tight areas, it fits various applications with features to lower cleaning costs and deliver an effective clean. Ideal for retail, hospitality venues, hospitals and factory workshops applications.



Compact and maneuverable design

Reach many areas of the facility and narrow spaces with the highly maneuverable scrubber with a 1m turning radius and front-mounted drive design.



Reduce risk of slips and falls

With a redesigned squeegee and integrated p-trap that improves water pick up and prevents water from streaking.



Improve environmental health in your facility

Easily access solution and recovery tanks for more effective cleaning and a yellow touch-point system for straightforward maintenance.

Inside the T560

- 1. Reduce maintenance costs** with recovery tank sensor that prevents any dirty water from reaching and damaging the vacuum motor and other key internal systems.
- 2. Multi-stage vacuum** for strong water pickup.
- 3. Clean tight spaces and narrow aisles** with T560's compact design and highly maneuverable handling.
- 4. Simplify post operation maintenance** with easily accessible solution and recovery tanks.
- 5. Reduce water drips** after cleaning operation with integrated p-trap debris collection system.
- 6. Simple no-tools, no-touch brush change system** for quick start up.



T560 specifications

FEATURE	SPECIFICATION
Cleaning path	700 mm
Productivity (per hour)*	4,200 m ² /hr
Scrubbing speed	6.0 kmh
Brush speed	150 rpm
Brush motor power	400W*2
Water suction motor	550 W
Solution tank capacity	70 L
Recovery tank capacity	75 L
Battery voltage	24V
Battery quantity (AGM)	2 pieces
Battery (AGM)	176AH at 10 hr
Dimensions (LxWxH)	1310 x 800 x 1240 mm
Weight (batteries not included)	164 kg
Weight (AGM battery included)	262 kg
Sound level (operator's ear)**	72 dBA

Specifications subject to change without notice.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

**Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA



PowerVac
CLEANING EQUIPMENT & SERVICE
www.powervac.com.au

PO Box 1031, Osborne Park DC, Western Australia, 6916
Cnr Hutton & Howe St, Osborne Park, Western Australia 6017

P ++61 8 9242 4751 **F** ++61 8 9242 4752
E info@powervac.com.au **ABN** 51 009 277 356